

Nozzles for Polymer Blowguns

0690 01 Standard Nozzle

	<p>Nickel-plated brass</p>	<p>C </p> <p>M12x1.25 2.5 0690 01 00</p>	<p>G L L1 kg</p> <p>15 31 9 0.024</p>
		<ul style="list-style-type: none"> Versatile use Progressive and powerful air jet <p> 327 NI/min 86 dBA 23° OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>	

0690 02 Safety Nozzle

	<p>Nickel-plated brass</p>	<p>C </p> <p>M12x1.25 2.5 0690 02 00</p>	<p>G L L1 kg</p> <p>15 31 9 0.024</p>
		<ul style="list-style-type: none"> Fluidised Powders Air screen effect Safety: avoids the nozzle becoming completely blocked <p> 315 NI/min 83 dBA 26° OSHA 1910.95 (b)/1910.242 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>	

0690 03 Straight Nozzle (Long)

	<p>Nickel-plated brass</p>	<p>C </p> <p>M12x1.25 2.5 0690 03 00</p>	<p>G L L1 kg</p> <p>15 332 307 0.068</p>
		<ul style="list-style-type: none"> Restricted Access Progressive and powerful air jet <p> 386 NI/min 82 dBA 21° OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>	

0690 04 Safety Straight Nozzle (Short)

	<p>Nickel-plated brass</p>	<p>C </p> <p>M12x1.25 2.5 0690 04 00</p>	<p>G L L1 kg</p> <p>15 102 77 0.033</p>
		<ul style="list-style-type: none"> Restricted Access Air screen effect and directional jet Safety: avoids the nozzle becoming completely blocked <p> 410 NI/min 82 dBA 21° OSHA 1910.242 (b)/ OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>	

0690 05 Angled Nozzle (Long)

	<p>Nickel-plated brass</p>	<p>C </p> <p>M12x1.25 2.5 0690 05 00</p>	<p>G L L1 kg</p> <p>15 316 292 0.065</p>
		<ul style="list-style-type: none"> Restricted or distant access Progressive and powerful air jet 360° rotation <p> 354 NI/min 82 dBA 21° OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>	