



A49B Series

3 to 5,5 HP



Air. Anytime. Anywhere.



Two-stage belt driven compressors

A49B series

Smaller size, higher efficiency

The air delivery of a 2-stage pump meets the compact size of a 1-stage pump

Efficiency

%75 efficiency on air delivery

Easy maintenance

Quick access to air filter

Ergonomic

Comfortable rubber handle

Safety

Fully enclosed plastic belt guard providing a physical barrier that prevents user from making contact with rotating machine parts and belt guard designed for easy belt replacement

Easy maintenance

Oil sight glass allowing a quick check on the oil level



Easy to move

Equipped with 360 degree rotating wheels



[@11 bar]



| Model | Code | L | Config. | l/min | HP | kW | rpm | Volt | Bar | dB(A) | LxPxA (mm) | kg |
|--------------------|------------|-----|---------|-------|-----|-----|------|----------|-----|-------|---------------|-----|
| PRO A49B 100 CM3 | 4116000250 | 100 | C | 444 | 3 | 2,2 | 1050 | 230/1/50 | 11 | 91 | 1006x486x927 | 70 |
| PRO A49B 150 CM3 | 4116000251 | 150 | C | 444 | 3 | 2,2 | 1050 | 230/1/50 | 11 | 91 | 1305x501x1006 | 84 |
| PRO A49B 200 CM3 | 4116000252 | 200 | C | 444 | 3 | 2,2 | 1050 | 230/1/50 | 11 | 91 | 1437x573x1058 | 109 |
| PRO A49B 270 FM3 | 4116000253 | 270 | F | 444 | 3 | 2,2 | 1050 | 230/1/50 | 11 | 91 | 1532x456x1005 | 118 |
| PRO A49B 270 FT3 | 4116000249 | 270 | F | 444 | 3 | 2,2 | 1050 | 400/3/50 | 11 | 91 | 1532x456x1005 | 118 |
| PRO A49B 100 CT3 | 4116000232 | 100 | C | 444 | 3 | 2,2 | 1050 | 400/3/50 | 11 | 91 | 1006x486x927 | 70 |
| PRO A49B 150 CT3 | 4116000233 | 150 | C | 444 | 3 | 2,2 | 1050 | 400/3/50 | 11 | 91 | 1305x501x1006 | 84 |
| PRO A49B 200 CT3 | 4116000234 | 200 | C | 444 | 3 | 2,2 | 1050 | 400/3/50 | 11 | 91 | 1437x573x1058 | 109 |
| PRO A49B BF4 | 4116000256 | BM | BF | 553 | 4 | 3 | 1300 | 400/3/50 | 11 | 93 | 738x430x563 | 54 |
| PRO A49B 200 CT4 | 4116000235 | 200 | C | 553 | 4 | 3 | 1300 | 400/3/50 | 11 | 93 | 1437x573x1047 | 105 |
| PRO A49B 270 CT4 | 4116000237 | 270 | C | 553 | 4 | 3 | 1300 | 400/3/50 | 11 | 93 | 1532x607x1128 | 120 |
| PRO A49B 200 FT4 | 4116000236 | 200 | F | 553 | 4 | 3 | 1300 | 400/3/50 | 11 | 93 | 1438x440x949 | 105 |
| PRO A49B 270 FT4 | 4116000238 | 270 | F | 553 | 4 | 3 | 1300 | 400/3/50 | 11 | 93 | 1532x456x1005 | 120 |
| PRO A49B 200 VT4 | 4116000239 | 200 | VT | 553 | 4 | 3 | 1300 | 400/3/50 | 11 | 93 | 737x638x1679 | 110 |
| PRO A49B 270 VT4 | 4116000240 | 270 | VT | 553 | 4 | 3 | 1300 | 400/3/50 | 11 | 93 | 737x600x1712 | 130 |
| PRO A49B 270 CM4 | 4116000254 | 270 | C | 553 | 4 | 3 | 1300 | 230/1/50 | 11 | 93 | 1532x607x1128 | 120 |
| PRO A49B BF5,5 | 4116000257 | BM | BF | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 738x430x563 | 60 |
| PRO A49B 200 CT5,5 | 4116000241 | 200 | C | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 1437x573x1058 | 114 |
| PRO A49B 270 CT5,5 | 4116000243 | 270 | C | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 1532x607x1132 | 124 |
| PRO A49B 500 CT5,5 | 4116000245 | 500 | C | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 1951x680x1269 | 191 |
| PRO A49B 200 FT5,5 | 4116000242 | 200 | F | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 1437x440x949 | 114 |
| PRO A49B 270 FT5,5 | 4116000244 | 270 | F | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 1532x456x1005 | 124 |
| PRO A49B 500 FT5,5 | 4116000246 | 500 | F | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 1950x530x1145 | 191 |
| PRO A49B 200 VT5,5 | 4116000247 | 200 | VT | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 737x637x1679 | 117 |
| PRO A49B 270 VT5,5 | 4116000248 | 270 | VT | 595 | 5,5 | 4 | 1400 | 400/3/50 | 11 | 95 | 736x600x1712 | 138 |

Multiple Configurations

Available both as base and tank mounted.

Product offer full portfolio including different tank sizes:

BM, 100 lt, 150 lt, 200 lt, 270 lt, 500 lt




QR code for enhanced product experience


1. Scan the custom QR code label with your phone.
2. Get access to tons of digital resources, such as product info, and tutorial videos.



A49B pump



B5900 pump



Application

Suitable for professional applications from wood/metal workshops to auto body shops & auto repair shop



Hammering



Screwing



Spray painting



Grinding



Drilling



Ratcheting



Extremely High Performance

Space-saving design as compact as a 1-stage pump.



Safer & More Comfortable

Narrow openings to prevent contact between hazardous moving parts and body or clothing + screws easy to reach for belt guard removal.



Performance design

The exclusive design of the belt guard improves the cooling air flow on the pumping unit.



Safety

Lockable pivoting wheels.