

Nakoda™ HOSE REELS

PRO SERIES 15 AIR/WATER

Air/Water 15 Metre

- Reinforced PVC braided hose
- Hose I.D. 12.5mm (1/2")
- Hose O.D. 18.5mm (3/4")
- Max working pressure 300 PSI (20 BAR)
- Hose outlet 1/2" BSPT male Brass swivel fitting


PRO SERIES 20 AIR/WATER

Air/Water 20 Metre

- Reinforced PVC braided hose
- Hose I.D. 9.5mm (3/8")
- Hose O.D. 16mm (5/8")
- Max working pressure 300 PSI (20 BAR)
- Hose outlet 3/8" BSPT male Brass swivel fitting




HELIX ULTRA-COIL®



Self layering hose system



Fixed or swivel mount



2 metre connecting hose



Nakoda™ HOSE REELS

Designed in Australia, Nakoda™ hose reels are supplied with the Helix Ultra Coil® self-layering hose system which will guide the main hose assembly with ease during hose pay-out and retrieval. The auto lock and auto rewind mechanism provides positive hose latching every full revolution of the hose inner drum. A pivoting wall bracket, main hose assembly and two metre connecting hose are supplied as standard giving a complete installation package. Constructed in UV stabilised Polypropylene, The Nakoda Pro Series in look, construction, performance and reliability; combined with a 2 year warranty make this a cost effective, professional hose reel for the industrial workspace.



The Nakoda™ Pro Series hose reels are heavy duty trade quality and can be used with compressed air or cold water.



Nakoda™ Pro Series Reel Product features and benefits

- **Designed in Australia**
- **High Impact, UV stabilised Polypropylene construction**
- **All units come complete with fitted main hose assembly and 2 metre connecting/feed hose**
- **Complete with fixed or 180° pivoting wall bracket**
Covers a larger span in the working area for increased control and ease of use
- **All units as standard include the Helix Ultra Coil® Technology self-layering hose system - for neat and tidy storage**
- **Lightweight material construction (Includes hose and pivoting wall bracket)**
- **Suitable for both compressed air and water (Up to 40°C)**
- **Fold flat carry handle convenient for moving about and installation and removal from a static position**
- **Hose guard supplied as standard, prevents hose kinking on the user end**
- **Swivel outlet fitting on all compressed air units**
- **Solid Brass main swivel shaft and hose fittings**
- **2 Year manufacturer's warranty**
(Excludes hose assemblies and seals)



ITEM CODE	MODEL	PRICE	HOSE ID	HOSE OD	HOSE MATERIAL	INLET	OUTLET	MAX WORKING PRESSURE	MAX TEMP	REEL/CASE TYPE	WEIGHT
HR-PS20-10AW	Nakoda Pro Series 20 C/W 20m x 10mm Air/Water Hose	£163.00	9.5mm (3/8")	16mm (5/8")	Reinforced PVC braided (Red)	3/8" BSP female Brass swivel	3/8" BSPT Brass	300 PSI (20 BAR)	140°F / 40°C	Polypropylene	9kg
HR-PS15-12AW	Nakoda Pro Series 15 C/W 15m x 12.5mm Air/Water Hose	£159.00	12.5mm (1/2")	18.5mm (3/4")	Reinforced PVC braided (Red)	1/2" BSP female Brass swivel	1/2" BSPT Brass	300 PSI (20 BAR)	140°F / 40°C	Polypropylene	9kg

For more information visit www.nakoda.co.uk