



Belt Drive - Lubricated - Vertical



WORKSHOP SERIES - STATIONARY

WORKSHOP SERIES - VERTICAL

The Vertical Workshop series incorporate all of the reliability and durability of a standard Workshop series assembled with a vertical air receiver designed for situations where space is at a premium. The vertical Workshop Series occupies 50% of the floor space when compared to the standard horizontal version. Four models are available as single phase 230V along with the larger three phase 400V versions.



| Belt Driven Lubricated - Vertical - Workshop Series Stationary | | | | | | | | | | | | | 1.5 to 7.5 kW | |
|--|---------------------------|------------|---------|-----|-----|-------|-----|-------------|-------|----------|-----|--------------|---------------|----|
| Code | Model | Type | Control | Rec | | Motor | | Capacity*** | | Pressure | | Dimension | | Kg |
| | | | | L | V | kW | HP | L/min | CFM | Bar | Psi | LxWxH (mm) | | |
| S-36HY504FPS149 | B3800B-PRO/150V FM3 2" UK | Stationary | DOL | 150 | 230 | 2.2 | 3 | 355 | 13.95 | 10 | 145 | 760x600x1980 | 116 | |
| TBC | B3800B-PRO/150V FT3 UK | Stationary | DOL | 150 | 400 | 2.2 | 3 | 355 | 13.95 | 10 | 145 | 760x600x1980 | 116 | |
| TBC | B3800B-PRO/150V FM4 UK | Stationary | DOL | 150 | 230 | 3 | 4 | 495 | 18 | 10 | 145 | 760x600x1980 | 118 | |
| S-N5NY701FPS070 | NB5/5.5FT/270V | Stationary | DOL | 270 | 400 | 4 | 5.5 | 640 | 22.9 | 11 | 160 | 860x850x2010 | 156 | |